



Product quality		
Formats		1209 x 225 x 5,3 mm
Packaging	Pack:	8 elements / 2,493 m ² / 19,66 kg
	Pallet:	42 packs / 91,4 m ² / 840,7 kg


Tolerances (Requirement EN 16511:2014)		
Squareness of the elements ($\leq 0.20\text{mm}$)		$\leq 0,15\text{ mm}$
Determination of Linearity ($\leq 0.30\text{ mm/m}$)		$\leq 0,20\text{ mm/m}$
Flatness concave / convex	lengthwise ($\leq 0.50/\leq 1.0\%$)	$\leq 0,30/\leq 0,50\%$
	wide ($\leq 0.15/\leq 0.20\%$)	$\leq 0,10/\leq 0,15\%$
Surface flushness	(average $\leq 0.10\text{ mm}$)	(average $\leq 0.10\text{ mm}$)
	(max. $\leq 0.15\text{ mm}$)	(max. $\leq 0.15\text{ mm}$)
Opening between installed elements	(average $\leq 0.15\text{ mm}$)	(average $\leq 0,05\text{ mm}$)
	(max. $\leq 0.20\text{ mm}$)	(max. $\leq 0.20\text{ mm}$)

Guarantee (according Parador guarantee conditions)		Notes
Domestic area	Commercial area	- suitable for all-over adhesion (see notes in our advisor)
15 years	5 years	- cleaning an maintenance see instructions
		- technical changes reserved




EN 14041:2004/AC:2006






















Quality
Production
Controlled
Functionality

www.tuv.com
ID: 000007615



Classification		
	Test method	Rating
 Utility class 23 domestic areas with intensive use	EN 16511	Living room, hall, kitchen, home office
 Utility class 31 commercial areas with low use	EN 16511	Hotels, small offices
 Reaction to fire	EN 13501-1	B _n -s1
 Slip resistance	EN 13893 EN 14041	$\mu \geq 0,30$ DS
 Staining resistance	EN 438-2	Category 1 + 2: level 5, no visible change Category 3: level 4, slight change
 Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6
 Resistance to roller castor chairs	EN 425	Type W, no visible changes (10.000 rev.)
 Thermal resistance Suitable for installation over underfloor heating when using an appropriate moisture barrier.	EN 12667	0,024 m ² *K/W
 Moving a furniture leg	EN 424	No visible changes
 Indentation-residual	EN ISO 24343-1	$\leq 0,05\text{ mm}$
 Formaldehyde emission (E1 = 0.1 ppm)	ISO 16000	< E1
 Acoustical - Impact noise reduction	EN ISO 10140	17 dB
 Length- and Square separating force	ISO 24334	lengthwise $\geq 4\text{ KN/m}$ transversely $\geq 3\text{ KN/m}$
 Abrasion	prEN 15468 Annex A	> 3.000 rev.
 Impact resistance	EN 13329 Annex F	$\geq 1.800\text{ mm}$
 Dimensional stability	EN ISO 23999	$\leq 0,15\%$
Micro scratch resistance	EN 16094	Method A MSR-A1
Antimicrobial activity	ISO 22196	Antibacterial
Slip resistance on an inclined plane	DIN 51130	Brushed texture: R 10
Disposal	EAK-Code-number	20 01 39
 Suitable for damp rooms: 100% waterproof product construction enables use in damp rooms (please observe installation instructions).		

Changed:	QMB Parador	File:	PA_TDS_Designboden_Vinyl_Basic_5.3_EN_20210201
Date:	15.12.2018	Latest update at:	https://parador.de/en/partner/downloads/index/cat/11/
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.02.2021