



















Product quality		
<b>Format</b>		1207 x 216 x 9,4 mm
<b>Packaging</b>	<b>Pack:</b>	7 elements / 1.825 m <sup>2</sup> / 17.00 kg
	<b>Palette:</b>	36 packs / 65.700 m <sup>2</sup> / 627.00 kg
Tolerances EN ISO 20326:2018		
<b>Squareness of the elements (≤ 0.20 mm)</b>		≤ 0,20 mm/m
<b>Determination of linearity (≤ 0.30 mm/m)</b>		≤ 0,15 mm/m
<b>Flatness concave / convex</b>	<b>lengthwise (≤ 0.50/≤ 1.0 %)</b>	≤ 0,35 / ≤ 1,0 %
	<b>wide (≤ 0.10/≤ 0.15 %)</b>	≤ 0,10 / ≤ 0,10 %
<b>Surface flushness</b>	<b>(average ≤ 0.10 mm)</b>	average ≤ 0.10 mm
	<b>(max. ≤ 0.15 mm)</b>	max. ≤ 0.15 mm
<b>Opening between installed elements</b>	<b>(average ≤ 0.15 mm)</b>	average ≤ 0.05 mm
	<b>(max. ≤ 0.20 mm)</b>	max. ≤ 0.10 mm
<b>Dimensional change due to changing air humidity % (≤ 0,25)</b>		≤ 0,1%
Guarantee (According Parador guarantee conditions)		Notes
Domestic area	Commercial area	- not suitable for all-over adhesion - cleaning and maintenance see instructions - technical changes reserved
15 years	5 years	
   		

Classification		
	Test method	Rating
 <b>Utility class 23</b> domestic areas with intensive use	EN ISO 20326	Living room, hall, kitchen, home office
 <b>Utility class 31</b> commercial areas with low use	EN ISO 20326	Hotels, small offices
 Wear layer	ISO 24340	0,3 mm
Surface Coating		PUR
 Reaction to fire	EN 13501-1	B <sub>n</sub> s1
 Slip resistance	EN 13893 EN 14041	μ ≥ 0,35 DS
 Staining resistance	EN 423	Grade 0, no visible changes
 Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6
 Resistance to roller castor chairs	ISO 4918	Type W, no visible changes
 <b>Thermal resistance</b> Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier.	EN ISO 10456	0,068 m <sup>2</sup> *K/W
 Moving a furniture leg	EN 424	No visible changes
 Indentation-residual	EN 433	≤ 0,10 mm
 <b>E1</b> Formaldehyde emission (E1 = 0.1 ppm)		≤ 0,05 ppm
 Acoustical - Impact noise reduction	ISO 717-2	15 dB (on Akustik-Protect 100) 16 dB (on PE film)
 Thickness swelling	ISO 24336 (≤ 18%)	≤ 16%
Antimicrobial activity	ISO 22196	Antibacterial
Slip resistance on an inclined plane	DIN 51130	Brushed, vivid texture: R 9 / Wood texture : R 10
Disposal	EAK-Code-number	17 02 03

Changed:	QMB Parador	File:	PA_TDS_Designboden_Vinyl_Basic-30_EN_20210201
Date:	01.06.2012	Latest update at:	<a href="http://www.parador.eu/service/catalogues-downloads/technical-data-sheets">www.parador.eu/service/catalogues-downloads/technical-data-sheets</a>
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.02.2021