















| Product quality | | |
|---|--------------------------|--|
| Format | 1219 x 229 x 2 mm | |
| Packaging | Pack: | 16 elements / 4,466 m ² / 17,680 kg |
| | Pallet: | 54 packs / 241.164 m ² / 984.720 kg |
| Tolerances EN ISO 10582 | | |
| Weight per unit area | ≥ 3.700 g/m ² | |
| Squareness of the elements (≤ 0.25 mm) | ≤ 0,10 mm/m | |
| Determination of linearity (≤ 0.35 mm/m) | ≤ 0,20 mm/m | |
| Dimensional stability after exposure to heat (≤ 0,15 %) | ≤ 0,15 % | |
| Curling after exposure to heat (≤ 1mm) | ≤ 1mm | |
| Guarantee (According Parador guarantee conditions) | | Notes |
| Domestic area | Commercial area | - only suitable for all-over adhesion - cleaning and maintenance see instructions - technical changes reserved |
| 15 years | 5 years | |
|  <small>EN 14041:2004/AC:2006</small> | |  |

| Classification | | | |
|---|--|----------------------|---|
| | | Test method | Rating |
|  | Utility class 23 domestic areas with intensive use | EN ISO 10582 | Living room, hall, kitchen, home office |
|  | Utility class 31 commercial areas with low use | EN ISO 10582 | Hotels, small offices |
|  | Wear layer | EN ISO 24340 | 0,3 mm |
| | Surface Coating | | PUR |
|  | Reaction to fire | EN 13501-1 | B _{f1} s1 |
|  | Slip resistance | EN 13893 EN 14041 | μ ≥ 0,30 DS |
|  | Staining resistance | ISO 26987 | Index 0, Not affected |
|  | Light fastness | EN ISO 105 - B02 | Blue wool scale: Stage ≥ 6 |
|  | Resistance to roller castor chairs | ISO 4918 | Type W, no visible changes |
|  | Thermal resistance Suitable for installation over underfloor heating | EN 12664 | 0,012 m ² *K/W |
|  | Moving a furniture leg | EN 424 | No visible changes |
|  | Indentation-residual | EN ISO 24343-1 | ≤ 0,10 mm |
| | Antimicrobial activity | ISO 22196 | Antibacterial |
| | Slip resistance on an inclined plane | DIN 51130 | Brushed, vivid texture: R 9 |
| | Disposal | EAK-Code-number | 20 01 39 |
|  | Suitable for damp rooms: 100% waterproof product construction enables use in damp rooms (please observe installation instructions). | | |

| | | | |
|--|-------------|-------------------|--|
| Changed: | QMB Parador | File: | PA_TDS_Designboden_Vinyl_Basic-2.0_EN_20210201 |
| Date: | 01.01.2018 | Latest update at: | www.parador.eu/service/catalogues-downloads/technical-data-sheets |
| Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from: | | | 01.02.2021 |